

# SPECIFICATION

Electronic Version 1.2.8

Stylesheet Version 1.0

## IMPROVED FLEXIBLE IMAGING MEMBER SEAM TREATMENT

### Cross Reference to Related Applications

This application is related to U.S. Patent Application Number \_\_\_\_\_ (Attorney Docket No. D/A2002Q), entitled FLEXIBLE IMAGING MEMBER SEAM TREATMENT APPARATUS, U.S. Patent Application Number \_\_\_\_\_ (Attorney Docket No. D/A2002Q1), entitled FLEXIBLE IMAGING MEMBER SEAM TREATMENT ARTICLE AND PREPARATION METHOD THEREOF, and U.S. Patent Application Number \_\_\_\_\_ (Attorney Docket No. D/A2002Q2), entitled FLEXIBLE IMAGING MEMBER SEAM TREATMENT APPARATUS, all filed on 29 May 2002 herewith, the disclosures of which are hereby incorporated by reference in their entirety. In addition, this application is related to U.S. Patent Application Serial No. 09/428,932, filed on 28 October 1999 in the names of Yu et al. and entitled SEAM STRESS RELEASE AND PROTRUSIONS ELIMINATION PROCESS, (Attorney Docket No. D/96182Q3), the entire disclosure of which is incorporated herein by reference.

### Background of Invention

[0001] Embodiments generally relate to a seam morphological improvement approach, and, more specifically, to a post ultrasonically-welded seam overcoat treatment for flexible imaging member belts.

[0002] Flexible electrostatographic belt imaging members are well known in the art. Typical electrostatographic flexible belt imaging members include, for example, photoreceptors for electrophotographic imaging systems, electroreceptors such as ionographic imaging members for electrographic imaging systems, and intermediate image transfer belts for transferring toner images in electrophotographic and electrographic imaging systems. These belts are usually formed by cutting a

rectangular, a square, or a parallelogram shape sheet from a web containing at least one layer of thermoplastic polymeric material, overlapping opposite ends of the sheet, and joining the overlapped ends together to form a welded seam. The seam extends from one edge of the belt to the opposite edge. Generally, these belts comprise at least a supporting substrate layer and at least one imaging layer comprising thermoplastic polymeric matrix material. The imaging layer as employed herein is defined as and refers to any of the dielectric imaging layer of an electroreceptor belt, the transfer layer of an intermediate transfer belt, and the charge transport layer of an electrophotographic belt. Thus, the thermoplastic polymeric matrix material in the imaging layer is generally located in the upper portion of a cross section of an electrostatographic imaging member belt, the substrate layer being in the lower portion of the cross section of the electrostatographic imaging member belt. Although the flexible belts of interest include the mentioned types, for simplicity reasons, the discussion hereinafter will be focus on the electrophotographic imaging member belts.

[0003] Between the substrate and imaging layers, such flexible electrophotographic imaging members or multilayered photoreceptors also typically include an electrically conductive layer, an optional hole blocking layer, an adhesive layer, a charge generating layer, and, in some embodiments, an anti-curl backing layer. One type of multilayered photoreceptor comprises a layer of finely divided particles of a photoconductive inorganic compound dispersed in an electrically insulating organic resin binder to form a layer that is charge generating and charge transporting. A typical layered photoreceptor having separate charge generating (photogenerating) and charge transport layers is described in U.S. Patent Number 4,265,990, the entire disclosure thereof being incorporated herein by reference. In negatively-charged varieties of such photoreceptors, a charge generating layer is capable of photogenerating holes and injecting the photogenerated holes into the charge transport layer.

[0004] Although excellent toner images can be obtained with multilayered belt photoreceptors, it has been found that as more advanced, higher speed electrophotographic copiers, duplicators and printers are developed, fatigue-induced cracking of the charge transport layer at the welded seam area is frequently

encountered during photoreceptor belt cycling. Moreover, the onset of seam cracking has also been found to rapidly lead to seam delamination due to fatigue, shortening belt service life. Dynamic fatigue seam cracking can possibly happen in ionographic imaging member belts as well.

[0005] As mentioned above, flexible electrostatographic imaging members are typically fabricated from a sheet cut from an imaging member web, generally in a rectangular or parallelogram shape, and a sheet is formed into a belt by joining overlapping opposite marginal end regions of the sheet. A seam is typically produced in the overlapping marginal end regions at the point of joining. Joining can be effected by any suitable means, such as by welding (including ultrasonic), gluing, taping, pressure heat fusing, and the like. Ultrasonic welding is generally the preferred method of joining because it is rapid, clean (no solvents), and produces a thin and narrow seam. In addition, ultrasonic welding is preferred because the mechanical pounding of the welding horn causes generation of heat at the contiguous overlapping end marginal regions of the sheet to maximize melting of one or more layers therein. A typical ultrasonic welding process is carried out by holding down the overlapped ends of a flexible imaging member sheet with vacuum against a flat anvil surface and guiding the flat end of an ultrasonic vibrating horn transversely across the width of the sheet, over and along the length of the overlapped ends, to form a welded seam.

[0006] When ultrasonically welded into a belt, the seam of multilayered electrophotographic imaging flexible members can occasionally contain undesirable high protrusions such as peaks, ridges, spikes, and mounds. These seam protrusions present problems during image cycling of the belt machine because they interact with cleaning blades to cause blade wear and tear, which ultimately affects cleaning blade efficiency and service life. Moreover, the protrusion high spots in the seam can also interfere with the operation of subsystems of copiers, printers and duplicators by damaging electrode wires used in development subsystems that position the wires parallel to and closely spaced from the outer imaging surface of belt photoreceptors. These closely spaced wires are employed to facilitate the formation of a toner powder cloud at a development zone adjacent to a toner donor roll and the imaging surface of the belt imaging member. Another frequently observed mechanical failure in the imaging belts during image cycling is that, after being subjected to extended bending

and flexing cycles over small diameter belt support rollers, the ultrasonically welded seam of an electrophotographic imaging member can develop cracks that propagate and lead to delamination of the belt. Additionally, such cracking and delamination can result from lateral forces caused by mechanical rubbing contact against stationary web edge guides of a belt support module during cycling. Seam cracking and delamination is further aggravated when the belt is employed in electrophotographic imaging systems utilizing blade cleaning devices and some operational imaging subsystems. Alteration of materials in the various photoreceptor belt layers such as the conductive layer, hole blocking layer, adhesive layer, charge generating layer, and/or charge transport layer to suppress cracking and delamination problems is not easily accomplished. The alteration of the materials can adversely impact the overall physical, electrical, mechanical, and other properties of the belt such as well as coating layer uniformity, residual voltage, background, dark decay, flexibility, and the like.

[0007] As mentioned above, when a flexible imaging member used in an electrophotographic machine is a photoreceptor belt fabricated by ultrasonic welding of overlapped opposite ends of a sheet, the ultrasonic energy transmitted to the overlapped ends melts the thermoplastic sheet components in the overlap region to form a seam. The ultrasonic welded seam of a multilayered photoreceptor belt is relatively brittle and low in strength and toughness. The joining techniques, particularly the welding process, can result in the formation of a splashing that projects out from either side of the seam in the overlap region of the belt. The overlap region and splashings on each side of the overlap region comprise a strip from one edge of the belt to the other that is referred herein as the seam region. The seam region of a typical overlap seamed flexible belt is about 1.6 times thicker than the thickness of the body of the belt. Because of the splashing, a typical flexible imaging member seamed belt has a peak splashing height of about 76 micrometers above the surface of the imaging layer at the junction between the top splashing and the surface of the belt. The junction meeting point is the undesirable site of physical discontinuity which has been found to act as a stress concentration point that facilitates early onset of seam cracking/delamination under the dynamic fatigue-inducing conditions to which imaging members are subjected in normal use.

[0008] The photoreceptor belt in an electrophotographic imaging apparatus undergoes bending strain as the belt is cycled over a plurality of support and drive rollers. The excessive thickness of the photoreceptor belt in the seam region due to the presence of the splashing results in a large induced bending strain as the seam travels over each roller. Generally, small diameter support rollers are highly desirable for simple, reliable copy paper stripping systems in electrophotographic imaging apparatus utilizing a photoreceptor belt system operating in a very confined space. Unfortunately, small diameter rollers, e.g., less than about 0.75 inch (19 millimeters) in diameter, raise the threshold of mechanical performance criteria to such a high level that photoreceptor belt seam failure can become unacceptable for multilayered belt photoreceptors. For example, when bending over a 19 millimeter diameter roller, a typical photoreceptor belt seam splashing can develop a 0.96 percent tensile strain due to bending. This is 1.63 times greater than a 0.59 percent induced bending strain that develops within the rest of the photoreceptor belt. Therefore, the 0.96 percent tensile strain in the seam splashing region of the belt represents a 63 percent increase in stress placed upon the seam splashing region of the belt.

[0009] Under dynamic fatiguing conditions, the seam provides a focal point for stress concentration and becomes the point of crack initiation which is further developed into seam delamination causing premature mechanical failure in the belt. Thus, the splashing tends to shorten the mechanical life of the seam and service life of the flexible member belts used in copiers, duplicators, and printers.

[0010] Although a solution to suppress the seam cracking/delamination problems has been successfully demonstrated, as described in a prior art, by a specific heat treatment process of a flexible electrophotographic imaging member belt with its seam parked directly on top of a 19 mm diameter back support rod for stress-releasing treatment at a temperature slightly above the glass transition temperature ( $T_g$ ) of the charge transport layer of the imaging member, nevertheless this seam stress release process was also found to produce various undesirable effects such as causing seam area imaging member set and development of belt ripples in the active electrophotographic imaging zones of the belt (e.g., the region beyond about 25.2 millimeters from either side from the midpoint of the seam). Moreover, the heat treatment can induce undesirable circumferential shrinkage of the imaging belt. The

set in the seam area of an imaging member mechanically adversely interacts with the cleaning blade and impacts cleaning efficiency. The ripples in the imaging member belt manifest themselves as copy printout defects. Further, the heat induced imaging belt dimensional shrinkage alters the precise dimensional specifications required for the belt. Another key shortcoming associated with the prior art seam stress release heat treatment process is the extensive heat exposure of a large seam area. This extensive heat exposure heats both the seam area of the belt as well as the rod supporting the seam. Since the belt must be cooled to below the glass transition temperature of the thermoplastic material in the belt prior to removal from the support rod to produce the desired degree of seam stress release in each belt, the heat treatment and cooling cycle time is unduly long and leads to very high belt production costs. Additionally, such seam heat treatment stress-release processing does not produce the desired seam surface smoothing and protrusion spot elimination.

[0011] Since there is no effective way to prevent the generation of localized high protrusions at the seam, imaging member belts are inspected, right after seam welding belt production process, manually by hand wearing a cotton glove through passing the index finger over the entire seam length and belts found catching the glove by the protrusions are identified as production rejects. Both the time consuming procedure of manual inspection and the number of seamed belts rejected due to the presence of high seam protrusions constitute a substantial financial burden on the production cost of imaging members.

[0012] The following references may be of interest:

[0013] U.S. Patent Number 5,190,608, issued 2 March 1993 to Darcy *et al.*, discloses a flexible belt having an outwardly facing surface, a welded seam having irregular protrusion on the outwardly facing surface and a thin flexible strip laminated and covering the welded seam and protrusions. This belt can be fabricated by providing a flexible belt having an outwardly facing surface and a welded seam having irregular protrusions on the outwardly facing surface and laminating a thin flexible strip to the welded seam. The belt can be used in an electrostatographic imaging process.

[0014] U.S. Patent Number 5,549,999, issued 27 August 1996 to Swain *et al.*, discloses a

process for coating flexible belt seams including providing a flexible belt having an outwardly facing surface and a welded seam, forming a smooth liquid coating comprising a hardenable film forming polymer on the welded seam, the coating being substantially free of fugitive solvent, and hardening the coating to form a smooth solid coating on the seam.

[0015] U.S. Patent Number 5,582,949, issued 10 December 1996 to Bigelow *et al.*, discloses a process for coating flexible belt seams including providing a flexible belt having an outwardly facing surface and a welded seam, forming a smooth liquid coating on the welded seam, the liquid coating comprising a film forming polymer and a fugitive liquid carrier in which the belt surface is substantially insoluble, and removing the fugitive liquid carrier to form a smooth solid coating on the seam.

[0016] U.S. Patent Number 6,328,922 B1, issued 11 December 2001 to Mishra *et al.*, discloses a process for post treatment of an imaging member belt including providing a support member having a smooth flat surface, providing a flexible belt having a welded seam, supporting the inner surface of the seam on the smooth flat surface, contacting the seam with a heated surface, heating the seam region with the heated surface to raise the temperature in the seam region to a temperature of from about 2 ° C to 20 ° C about the T<sub>g</sub> of the thermoplastic polymer material, and compressing the seam with the heated surface with sufficient compression pressure to smooth out the seam.

[0017] U.S. Patent Number 5,552,005, issued 3 September 1996 to Mammino *et al.*, discloses a flexible imaging sheet and a method of constructing a flexible imaging sheet. The method of constructing a flexible imaging sheet comprises overlapping, joining, and shaping first and second marginal end regions of a sheet to form an overlap region and a non-overlap region joined to one another by a seam in the overlap region with a generally planar surface co-planar with a surface of the non-overlap region. The first and second marginal end regions are secured to one another in the overlap region by the seam, and are substantially co-planar to minimize stress on the flexible imaging sheet. Minimization of stress concentration, resulting from dynamic bending of the flexible imaging sheet during cycling over a roller within an electrophotographic imaging apparatus, is particularly accomplished in the present

invention.

[0018] U.S. Patent Number 6,074,504 to Yu *et al.*, issued 13 June 2000, discloses a process for treating a seamed flexible electrostatographic imaging belt including providing an imaging belt having two parallel edges, the belt comprising at least one layer comprising a thermoplastic polymer matrix and a seam extending from one edge of the belt to the other, the seam having an imaginary centerline, providing an elongated support member having an arcuate supporting surface and mass, the arcuate surface having at least a substantially semicircular cross section having a radius of curvature of between about 9.5 millimeters and about 50 millimeters, supporting the seam on the arcuate surface with the region of the belt adjacent each side of the seam conforming to the arcuate supporting surface of the support member, precisely traversing the length of the seam from one edge of the belt to the other with thermal energy radiation having a narrow Gaussian wavelength distribution of between about 10.4 micrometers and about 11.2 micrometers emitted from a carbon dioxide laser, the thermal energy radiation forming a spot straddling the seam during traverse, the spot having a width of between about 3 millimeters and about 25 millimeters measured in a direction perpendicular to the imaginary centerline of the seam, and rapidly quenching the seam by thermal conduction of heat from the seam to the mass of the support member to a temperature below the glass transition temperature of the polymer matrix while the region of the belt adjacent each side of the seam conforms to the arcuate supporting surface of the support member.

[0019] While these and other innovative prior art approaches provided improved flexible belt seam morphology, nevertheless it has been found that solution of one problem has also created new undesirable issues. For example, overcoating the seam of a photoreceptor belt with metallic foil can cause electrical seam arcing as the belt cycles beneath a charging device during electrophotographic imaging processes. Additionally, application of liquid overcoating layer over the seam induced charge transport molecule crystallization in the vicinity of the seam overcoat, not to mention that liquid overcoating layer can produce poor adhesion bond strength to the seam after solidification into a dried coat. Thus, there is a continuing need for electrostatographic imaging belts having improved welded seam design that is resistant to seam cracking/delamination, substantially free of seam protrusions, has

improved seam region physical continuity, and is substantially free of factors that damage imaging subsystems.

[0020] Furthermore, there is an urgent need to provide seamed flexible imaging belts with an improved seam morphology which can withstand greater dynamic fatigue conditions thereby extending belt service life. It is also important, from the imaging member belt production point of view, that effective cutting of unit manufacturing cost of seamed imaging belts can be realized if an innovative post seaming treatment process can be developed and adopted for belt finishing implementation to provide the improvement of morphological seam surface smoothing free of protrusion spots and to effect the elimination of physical discontinuity at the junction meeting point where the top seam splashing making contact with the belt surface.

[0021] Embodiments of the instant invention provide such an improved electrostatographic imaging member that substantially overcomes the above-noted deficiencies by providing a morphologically improved seamed electrostatographic imaging member. Embodiments yield an improved electrostatographic imaging member with an ultrasonically welded seam which, after being subjected to post processing, exhibits greater resistance to onset of dynamic fatigue induced seam cracking/delamination problem. After being subjected to post processing according to embodiments, seams exhibit good circumferential dimension tolerance, robust mechanical seam function, and reduced cleaning blade wear. Seams treated according to embodiments are substantially free of seam protrusions, have smoother surface morphological profiles, have little or no seam region physical discontinuity, and have reduced seam area thickness that greatly reduces seam region bending stress when the electrostatographic imaging member flexes over small-diameter belt module support rollers.

[0022] These results are achieved according to embodiments by, for example, providing a flexible imaging member seam treatment method comprising bonding a thermoplastic polymer film to the seam of the flexible imaging member after placing the film on the seam; bonding comprises heating the film above a glass transition temperature of at least one of a thermoplastic polymer from which the film is made and a polymer from which an imaging layer of the flexible imaging member is made. This method can

further comprise applying pressure to the film by exerting a compressive pressure of between about 70 lbs/in<sup>2</sup> and about 770 lbs/in<sup>2</sup> on the film and seam. Additionally, the method can include removing a substrate supporting the thermoplastic polymer film after bonding where a support substrate is used. The thermoplastic polymer film can be blended into the imaging layer as a result of the treatment, particularly by providing a thermoplastic polymer film compatible with the polymer of the imaging layer.

[0023] Such results can also be achieved according to embodiments by, for example, providing a flexible imaging member seam treatment method comprising providing a treatment strip including a thermoplastic polymer layer, placing the treatment strip over a seam of a photoreceptor belt with the thermoplastic polymer layer contacting the seam, applying pressure and heat to the strip, and removing the pressure and heat from the strip after sufficient time has passed for the thermoplastic polymer to bond to the seam. The treatment strip can include a thermoplastic polymer film, such as a polycarbonate, and can be supported by a high-temperature-resistant removable substrate, such as a high-transition-temperature flexible polymeric film or a flexible metallic film. Further, the thermoplastic polymer film can include a charge transport compound to better match the composition of the imaging layer of the flexible imaging member seam being treated.

[0024] Such results can further be achieved according to embodiments by, for example, providing a flexible imaging member seam treatment method comprising placing a flexible imaging member seam region on a support surface, placing a thermoplastic polymer film on the seam region, and heating the thermoplastic polymer film to a temperature falling in the range of from about 20 ° C to about 70 ° C above a glass transition temperature of at least one of a thermoplastic polymer of the thermoplastic polymer film and a polymer of an imaging layer of the flexible imaging member. Placing a thermoplastic polymer film on the seam region can further comprise forming a treatment article including the thermoplastic polymer film on a substrate and placing the treatment article on the seam region with the thermoplastic polymer film in contact with the seam region. Forming a treatment article can comprise providing a substrate comprising a high-temperature-resistant material, such as a flexible metallic film or a high-glass-transition-temperature flexible polymeric film like a

biaxially-oriented PET film. The thermoplastic polymer film can comprise a thermoplastic polymer selected to form a polymer blend with a polymer from which the flexible imaging member is made. Heating the thermoplastic polymer film can comprise directing infrared radiation at the thermoplastic polymer film, such as with a lamp or infrared laser, or can comprise applying a heated element. When applying a heated element, the heated element can also apply pressure.

[0025] Additionally, such results can be achieved according to embodiments by, for example, providing an ultrasonically welded seamed flexible imaging member seam treatment process comprising:

[0026] providing an elongated support member having a smooth supporting surface;

[0027] providing a flexible belt having parallel edges and a welded seam extending from one edge to another edge, the belt seam including a seam region with an overlap and two adjacent splashings, the belt comprising a thermoplastic polymer material having a glass transition temperature, and inner and outer surfaces;

[0028] supporting the inner surface of the seam region on the smooth supporting surface with the seam region of the belt conforming to the supporting surface of the support member;

[0029] placing a thermoplastic polymer strip comprising a same material as a binder polymer of a top imaging layer directly of the seam region over the seam;

[0030] contacting the polymer strip above the seam with a heated surface comprising a smooth material with at least one of a low surface energy and an adhesive property with a profile that is substantially parallel to the smooth supporting surface;

[0031] heating the strip to a temperature of from about 20 ° C to about 70 ° C above a glass transition temperature ( $T_g$ ) of at least a lower of the thermoplastic polymer material and the top imaging layer; and

[0032] compressing the strip above the seam with the heated surface to effect at least one of overcoat lamination, protrusion reduction, surface profile smoothing, seam region physical continuity enhancement, and seam region thickness reduction.

[0033] Although this invention deals with the seam overcoat material formulations, it also relates to apparatus and lamination process for effective flexible electrostatographic imaging member belts seam overcoating application, the following will focus only on seamed flexible electrophotographic imaging member belts to simplify discussion.

[0034] A more complete understanding of the process and apparatus of the present invention can be obtained by reference to the accompanying drawings wherein:

[0035]

### Brief Description of Drawings

[0036] In the detailed description, reference is made to the accompanying drawings, in which:

[0037] FIG. 1 illustrates a schematic partial cross-sectional view of a multiple layered flexible sheet of electrophotographic imaging member material with opposite ends overlapped.

[0038] FIG. 2 shows a schematic partial cross-sectional view of a multiple layered seamed flexible electrophotographic imaging member belt derived from the sheet illustrated in FIG. 1 after ultrasonic seam welding.

[0039] FIG. 3 illustrates a schematic partial cross-sectional view of a multiple layered seamed flexible electrophotographic imaging member belt which has mechanical failure due to fatigue induced seam cracking/delamination problem.

[0040] FIG. 4 shows the cross sectional side view of a strip laminator consisting of a thin thermoplastic polymer laminate lightly adhering over a flexible carrier backing substrate layer readily for use in invention seam overcoating application.

[0041] FIG. 5 is a schematic sectional side view of a seamed flexible electrophotographic imaging member belt in which the seam is held down onto the flat supporting surface of an elongated support member, with a strip laminator (not shown) positioned directly over the seam, while subjected to an elevated temperature seam overcoating/lamination process, utilizing a flat surfaced narrow heating and compression bar.

[0042] FIG. 6 shows an isometric, schematic view of a seamed flexible electrophotographic imaging member belt in which the seam is parked on, with a strip laminator placed directly over the seam, and held on a flat surface of an elongated support member while subjected to an alternative seam overcoating/lamination process, utilizing a hot rolling compression wheel.

[0043] FIG. 7 is an isometric schematic view of a seamed flexible electrophotographic imaging member belt in which the seam is parked on and held against the arcuate convex surface of an elongated support member by vacuum, while heating with a focus infrared red spot and coupled with a compression rolling wheel, is subjected to the heating and compression processing of the present invention to yield seam overcoating/lamination and stress-release results.

[0044] FIG. 8 illustrates the schematic, sectional side view of the seam overcoating/lamination processing arrangement of FIG. 7, but with the only exception that this exemplary embodiment used instead a CO<sub>2</sub> laser heat radiation source to replace the IR heating source shown in FIG. 7 for achieving the very same invention result.

[0045] FIG. 9 shows the isometric, schematic view of a seamed flexible electrophotographic imaging member belt in which the seam is parked on and held over the arcuate convex surface of an elongated support member by vacuum while subjected to another invention variance seam overcoating/lamination processing, utilizing a hot rolling compression wheel.

[0046] In the drawings and the following description below, it is to be understood that like numeric designations refer to components of like function.

## Detailed Description

[0047] Although specific terms are used in the following description for the sake of clarity, these terms are intended to refer only to the exemplary embodiment selected for illustration in the drawings, and are not intended to define or limit the scope of invention.

[0048] Referring to FIG. 1, there is illustrated a flexible electrophotographic imaging

member 10 in the form of a belt formed from a sheet having a first end marginal region 12 overlapping a second end marginal region 14 to form an overlap region ready for a seam forming operation. The flexible electrophotographic member 10 can be used within an electrophotographic imaging device and can be a single film substrate member or a member having a film substrate layer combined with one or more additional coating layers. At least one of the coating layers comprises a film forming binder.

[0049] The flexible electrophotographic imaging member 10 can be a single layer or comprise multiple layers. If the flexible electrophotographic imaging member 10 is to be a negatively charged photoreceptor device, the flexible electrophotographic imaging member 10 may comprise a charge generator layer sandwiched between a conductive surface and a charge transport layer. Alternatively, if the flexible imaging member 10 is to be a positively charged photoreceptor device, the flexible imaging member 10 may comprise a charge transport layer sandwiched between a conductive surface and a charge generator layer.

[0050] The layers of the flexible electrophotographic imaging member 10 can comprise numerous suitable materials having suitable mechanical properties. Examples of typical layers are described in U.S. Patent Number 4,786,570, U.S. Patent Number 4,937,117, and U.S. Patent Number 5,021,309, the entire disclosures of which are incorporated herein by reference. The flexible electrophotographic imaging member 10 of embodiments shown in FIG. 1 comprises, from top to bottom, a charge transport layer 16, a generator layer 1, an interface layer 20, a blocking layer 22, a conductive ground plane layer 24, a supporting layer 26, and an anti-curl back coating layer 28. It should be understood that the thicknesses of the layers are conventional and that a wide range of thicknesses can be used for each of the layers.

[0051] The end marginal regions 12 and 14 can be joined by any suitable means including gluing, taping, stapling, pressure and heat fusing to form a continuous member such as a belt, sleeve, or cylinder. However, for ease of belt fabrication, short operation cycle time, and the mechanical strength of the fabricated joint, embodiments employ an ultrasonic welding process to join the end marginal regions 12 and 14 into a seam 30 in the overlap region, as shown in FIG. 2, to form a seamed

flexible electrophotographic imaging member 10 in the form of a belt. In the ultrasonic seam welding process, ultrasonic energy applied to the overlap region is used to melt suitable layers such as the charge transport layer 16, generator layer 18, interface layer 20, blocking layer 22, part of the support layer 26 and/or anti-curl back coating layer 28. Direct fusing of the support layer achieves optimum seam strength.

[0052] Upon completion of welding the overlap region of the flexible electrophotographic imaging member sheet into a seam 30 using ultrasonic seam welding technique, the overlap region is transformed into an overlapping and abutting region as illustrated in FIGS. 2 and 3. Within the overlapping and abutting region, the portions of the flexible electrophotographic imaging member 10, which once formed the end marginal regions 12 and 14, are joined by the seam 30 such that the once end marginal regions 12 and 14 are overlapping and abutting one another. The seam 30, indicated by a dashed line in FIG. 2, comprises two vertical portions joined by a horizontal portion. The midpoint of seam 30 can be represented by an imaginary centerline extending the length of seam 30 from one edge of belt 10 to the opposite edge, the imaginary centerline (not shown) running along the middle of the horizontal portion which joins the two vertical portions illustrated in FIG. 2. In other words, a plan view (not shown) of the horizontal portion of seam 30 would show a strip much like a two lane highway in which the centerline would be represented by the white divider line separating the two lanes, the two lanes comprising end marginal regions 12 and 14. The flexible electrophotographic imaging member 10 has a first major exterior surface or side 32 and a second major exterior surface or side 34 on the opposite side. The seam 30 joins the flexible electrophotographic imaging member 10 so that, the bottom surface 34 at and/or near the first end marginal region 12 is integral with the top surface 32 at and/or near the second end marginal region 14. Generally, the bottom surface 34 includes at least one layer immediately above the bottom of the belt in the first end marginal region 12, and the top surface 32 includes including at least one layer immediately below the top of the belt in the second end marginal region 14.

[0053] The welded seam 30 in embodiments also contains upper and lower splashings 68 and 70 at each end thereof as illustrated in FIGS. 2 and 4. The splashings 68 and 70 are formed in the process of joining the end marginal regions 12 and 14 together

when molten material is necessarily ejected from either side of the overlap region to facilitate direct support-layer-to-support-layer fusing. The upper splashing 68 is formed and positioned above the overlapping end marginal region 14, abutting the top surface 32 and adjacent to and abutting the overlapping end marginal region 12. The lower splashing 70 is formed and positioned below the overlapping end marginal region 12, abutting bottom surface 34 and adjacent to and abutting the overlapping end marginal region 14. The splashings 68 and 70 extend beyond the sides and the edges of the seam 30 in the overlap region of the welded flexible electrophotographic imaging member 10. The extension of the splashings 68 and 70 beyond the sides and the edges of the seam 30 is undesirable for many machines such as electrophotographic copiers, duplicators, and other such machines that require precise edge positioning of a flexible electrophotographic imaging member 10 during machine operation. Generally, the extension of the splashings 68 and 70 at the belt edges of the flexible electrophotographic imaging member 10 are removed by a notching operation.

[0054] A typical upper splashing 68 has a height or thickness  $t$  of about 90 micrometers and projects about 17 microns above the surface of the overlapping end marginal region 12. Each of the splashings 68 and 70 has an uneven, but generally rectangular, shape including one side 72, a free side that forms a free end, extending inwardly toward top surface 32 from an outwardly facing side 74, which extends substantially parallel to either the top surface 32 or the bottom surface 34. The free side 72 of the splashing 68 forms an approximately perpendicular angle  $\theta_1$  with the bottom surface 34 of the flexible electrophotographic imaging member 10 at a junction 76. Likewise, the free side 72 of the splashing 70 forms an approximately perpendicular angle  $\theta_2$  at a junction 78 of the free side 72 of the lower splashing 70 and the bottom surface 34 of the flexible imaging member 10. Both junctions 76 and 78 create focal points for stress concentration and become initial points of failure affecting the mechanical integrity of the flexible electrophotographic imaging member 10.

[0055] During machine operation, the seamed flexible electrophotographic imaging member 10 cycles or bends over rollers, particularly small diameter rollers, of a belt support module within an electrophotographic imaging apparatus. As a result of dynamic bending/flexing of the flexible electrophotographic imaging member 10

during cycling, the rollers repeatedly exert a force on the flexible imaging member 10 that causes large stresses to develop generally adjacent to the seam 30 due to the excessive thickness and material discontinuity thereof. The stress concentrations that are induced by bending near the junction points 76 and 78 can reach values much larger than the average value of the stress over the entire length of the flexible electrophotographic imaging member 10. The induced bending stress is inversely related to the diameters of a roller that the flexible imaging member 10 bends over and directly related to the thickness of the seam 30 of the flexible electrophotographic imaging member belt 10. When a structural member, such as the flexible electrophotographic imaging member 10, contains a sudden increase in cross-sectional thickness at the overlap region, high localized stress occurs near the discontinuity, e.g. junction points 76 and 78.

[0056] When the flexible electrophotographic imaging member 10 bends over the rollers of a belt module within an electrophotographic imaging apparatus, the bottom surface 34 of the flexible electrophotographic imaging member 10, which is adapted to contact the exterior surface of the roller, is compressed. In contrast, the top surface 32 is stretched under tension. This is attributable to the fact that the top surface 32 and bottom surface 34 move in a circular path about the circular roller. Since the top surface 32 is at greater radial distance from the center of the circular roller than the bottom surface 34, the top surface 32 must travel a greater distance than the bottom surface 34 in the same time period. Therefore, the top surface 32 must be stretched under tension relative to a generally central portion of the flexible electrophotographic imaging member 10 (the portion of the flexible electrophotographic imaging member 10 generally extending along the center of gravity of the flexible imaging member 10). Likewise, the bottom surface 34 must be compressed relative to the generally central portion of the flexible imaging member 10 (the portion of the flexible electrophotographic imaging member 10 generally extending along the center of gravity of the flexible electrophotographic imaging member 10). Consequently, the bending stress at the junction point 76 will be tension stress, and the bending stress at the junction point 78 will be compression stress.

[0057] Compression stresses, such as at the junction point 78, rarely cause seam 30 failure. Tension stresses, such as at junction point 76, however, are much more of a

problem. The tension stress concentration at the junction point 76 in great likelihood will eventually result in crack initiation through the electrically active layers of the flexible electrophotographic imaging member 10 as illustrated in FIG. 3. The illustrated crack 80 is adjacent to the top splashing 68 of the second end marginal region 14 of the flexible electrophotographic imaging member 10. The generally vertically extending crack 80 initiated in the charge transport layer 16 continues to propagate through the generator layer 18. Inevitably, the crack 80 extends generally horizontally to develop seam delamination 81 which is propagated through the relatively weak adhesion bond between the adjoining surfaces of the generator layer 18 and the interface layer 20.

[0058] The formation of the local seam delamination 81 is typically called seam puffing. The excess thickness of the splashing 68 and stress concentration at the junction 76 causes the flexible electrophotographic imaging member 10 to perform, during extended machine operation, as though a material defect existed therein. Thus, the splashing 68 tends to promote the development of dynamic fatigue failure of the seam 30 and can lead to separation of the joined end marginal regions 12 and 14 severing the flexible imaging member 10. Consequently, the service life of the flexible imaging member 10 is shortened.

[0059] In addition to seam failure, the crack 80 acts as a depository site and collects toner, paper fibers, dirt, debris, and other unwanted materials during electrophotographic imaging and cleaning of the flexible electrophotographic imaging member 10. For example, during the cleaning process, a cleaning instrument, such as a cleaning blade, will repeatedly pass over the crack 80. As the site of the crack 80 becomes filled with debris, the cleaning instrument dislodges at least some portion of this highly concentrated level of debris from the crack 80. The amount of the debris, however, is beyond the removal capacity of the cleaning instrument, and portions of the highly concentrated debris are deposited onto the surface of the flexible electrophotographic imaging member 10. In effect, the cleaning instrument spreads the debris across the surface of the flexible electrophotographic imaging member 10 instead of removing the debris therefrom.

[0060] In addition to seam failure and debris spreading, the portion of the flexible

member 10 above the seam delamination 81, in effect, becomes a flap which moves upwardly. The upward movement of the flap presents an additional problem during the cleaning operation. The flap becomes an obstacle in the path of the cleaning instrument as the instrument travels across the surface of the flexible electrophotographic imaging member 10. The cleaning instrument eventually strikes the flap when the flap extends upwardly. As the cleaning instrument strikes the flap, great force is exerted on the cleaning instrument which can lead to damage thereof, e.g., excessive wear and tearing of the cleaning blade.

[0061] In addition to damaging the cleaning blade, the striking of the flap by the cleaning instrument causes unwanted vibration in the flexible electrophotographic imaging member 10. This unwanted vibration adversely affects the copy/print quality produced by the flexible electrophotographic imaging member 10. The copy/print is affected because imaging occurs on one part of the flexible imaging member 10 simultaneously with the cleaning of another part of the flexible imaging member 10.

[0062] To overcome the problems associated with seam cracking and delamination, embodiments employ a seam treatment article, treatment strip, or laminator strip 32 applied in a strip to the seam region in a particular fashion. A laminator strip 32 according to embodiments, shown, for example, in cross-section in FIG. 4, comprises a film or thin laminate 34 adhering to a flexible backing substrate layer 36. Embodiments employ a thickness of the laminate 34 of between about 5 micrometers and about 50 micrometers; particularly, good results can be achieved with a thickness of between about 10 micrometers and about 30 micrometers.

[0063] Laminate 34 is a film-forming thermoplastic polymer that, in embodiments, is substantially identical or substantially compatible with (compatible means it can form polymer blend) the polymer binder of the charge transport layer of the flexible imaging member. In this context, compatible means that the thermoplastic polymer film 34 can form a polymer blend with the polymer binder of the charge transport layer. Alternatively, embodiments can employ a laminate 34 that is a polymer blend of the polymer binder and a film-forming thermoplastic polymer. In addition, the laminate 34 of embodiments can contain organic charge transport molecule of the same kind or of a different kind as that of the charge transport layer. The laminate 34

of embodiments can have a width of from about 2 mm to about 15 mm, but can yield better results with a width of between about 3 and about 10 mm. The laminate 34 must be compressible and malleable under the heat and compression processing conditions to enable bonding to the seam and facilitate filling the physical discontinuities of the seam.

[0064] Although the flexible backing substrate layer 36 can be a metallic foil or a high glass transition temperature ( $T_g$ ) flexible polymer substrate, use of a polymer substrate that is substantially not affected by the heat and compression of embodiments is preferred. Materials such as polyethylene terephthalate (PET, also known as Mylar), polyethylene naphthalate (Kadelex), polyimide (Kapton), and the like meet such requirements and can be used in embodiments. A thickness of between about 2 mils and about 5 mils is satisfactory in embodiments, and a width equal to the width of the laminate can be employed, with even better seam overcoating/lamination results achieved in embodiments having a substrate about 2 to about 5 mm wider on each side of the laminate 34. The laminate 34 preferably has, in embodiments, an 180° adhesion peel strength over the backing substrate layer 36 of between about 3 g/cm and about 8 g/cm to ensure that the substrate can be readily stripped off of the overcoat after completion of the treatment process. Although in embodiments the laminator strip 32 is preferred to be a dual-layer strip as illustrated in FIG. 4, it can also be just a single laminate layer 34 if desired.

[0065] An apparatus for carrying out embodiments of the treatment method includes a heat source or heating means that heats the seam region (the area of the imaging member 10 around the seam 30) after the laminate has been placed in contact with the seam. Embodiments also include means for applying pressure to the heated region. In embodiments, as shown in FIG. 5, a hot compression bar or plate 145 is the heat source and provides localized heating and compression of the region about the seam 30, directly over which a laminator strip (not shown) has been placed, to yield seam overcoating/lamination result. Embodiments also include means to hold the seam region in place during treatment, such as a vacuum system. Thus, while the seam 30 of imaging member 10 is positioned and vacuum held down on the flat smooth supporting surface of support member 138, the heat source heats the seam region and strip. The hot compression bar 145, preferably metallic, has a smooth

outer contacting surface that is coated with a thin adhesive or low surface energy coating to prevent imaging layer material and the laminator strip from adhering to its surface when seam overcoating/lamination processing is carried out. Any suitable adhesive or low surface energy material can be employed, including fluoropolymers, such as Teflon, silicone, polyimide, and the like. A thin Teflon coating on the smooth contacting surface is preferred in embodiments because it promotes ease of release and prevents imaging member material from sticking to the surface of the heating/compression bar 145 when making compression contact during seam lamination processing treatment. The efficiency of heat energy delivery from the heating/compression bar 145, preferably comprising resistance elements (not shown) temperature control, to the laminator strip and seam area during contact is adjusted by any suitable device, such as a conventional adjustable variac 132, to provide sufficient power to raise the temperature of the laminator strip and seam area from about 20 ° C to 70 ° C above the  $T_g$  of the thermoplastic polymer material in the charge transport layer ( $T_g$  of the laminate if it is lower than that of the charge transport layer) of the electrophotographic imaging member 10. This thermoplastic polymer material is the top layer of the imaging member, which is for example the charge transport layer comprising a polymer binder with dissolved or molecularly dispersed charge transport compound, of electrophotographic imaging member. Conventional thermostats can be employed to regulate the temperature of the heating/compression bar 145

[0066]

A narrow vacuum channel 140 can be used in embodiments on each side of the support member to vacuum hold the belt 10 down against the flat supporting surface of support member 138. The vacuum channels 140 can be about 25 millimeters apart and extend, on each side of seam 30, along the support member 138 to about the full width of the belt 10. Suitable widths for the vacuum channels can be about 60 mils (1.5 mm). The upper ends of the vacuum channels 140 are open, and the lower ends are connected by a suitable device, such as a valved flexible hose (not shown), leading to any suitable vacuum source. After belt 10 is placed onto support member 138, such as manually or by any suitable conventional robotic device, the initially closed valve on the flexible hose to the vacuum source is opened, enabling the device to suck the belt 10 against the upper, flat, smooth surface of support member 138. This

suction holds the belt 10 substantially immobile on support member 138 during seam overcoating/lamination processing. If desired, embodiments can include a plurality of holes of any suitable shape (e.g. round, oval, square, and the like) instead of or in addition to the channels 140. The number and size of the holes should be sufficient hold the belt 10 against the support member. The size of the channels and holes should be small enough to avoid distortion of the belt during the seam area heating and compression process. The resistance of the belt to distortion when suction is applied depends on the beam strength of the specific belt employed, which in turn depends upon the specific materials in and thickness of the layers in the belt 10. The support member 138 may comprise any suitable hard material. Typical materials include, for example, hard plastic, having a smooth and polished surface. Preferably, support member 138 is metallic.

[0067]

In embodiments, the heating/compression bar 145 preferably has a width of between about 6 millimeters and about 30 millimeters with a length sufficient to cover the seam 30 along the entire width of the imaging member 10. In the process, heating/compression bar 145 compresses against laminator strip and seam 30 to make intimate force contact with the seam. Such intimate force contact made by heating/compression bar 145 substantially instantaneously elevates the temperature of a small localized region of the imaging layer adjacent to seam 30 of the imaging member containing thermoplastic polymer. This small localized region of the imaging layer in the upper portion of the seam region is heated substantially instantly above the  $T_g$  of the thermoplastic polymer. Typically, the  $T_g$  of a film forming polymer used for an electrophotographic imaging layer, e.g., the charge transport layer, is at least about 45 ° C to satisfy most imaging belt machine operating conditions. The imaging layer of an imaging member is a charge transport layer if the imaging member is an electrophotographic imaging member and a dielectric layer if the imaging member is an electrographic imaging member. Since the charge transport layer of embodiments is a composite comprising a polymer binder, a dissolved or molecularly dispersed charge transport organic compound, and optional pigment particles, the  $T_g$  in this case is a  $T_g$  of the combination. Thus, the expression polymer material as employed herein is defined as the polymer and any other material present in an imaging layer or in the laminate. Such polymer materials used for

electrophotographic imaging layer coating applications normally have a  $T_g$  of at least about 45 ° C to satisfy most imaging belt machine operating conditions. Preferably, the seam area heating and compression process is carried out between about 20 ° C and about 70 ° C above the  $T_g$  of the thermoplastic polymer material of the imaging layer (e.g., charge transport layer) or the laminate (whichever one has the lower  $T_g$ ) in order to yield strong overcoated laminate adhesion bonding onto the seam region, surface smoothing result, good physical continuity transition at the seam region, and seam region thickness reduction outcome. Occurrence of material melting, distortion, or cutting through of the seam components during heat/compression processing treatment should be avoided, because this weakens or damages the belt.

[0068] For processing a flexible imaging member having a skewed seam, the belt itself can be cocked and adjusted such that the seam is positioned, without skewing, on the flat support member 138 and under the heating/compression bar 145. Compression bar 145 contacts and compresses the laminator strip and seam 30 while the belt 10 is held down against the flat supporting surface of the support member 138 by the vacuum channels 140. During pressure contact, the heat conduction from the hot compression bar 145 heats up the seam region to the desirable temperature and the compression pressure generated by the bar facilitates the bonding of the laminate to the seam to provide surface smoothing, eliminate or minimize seam region physical discontinuity, as well as reduce seam region thickness. The compression bar 145 preferably exerts a compressive pressure of between about 70 lbs/in<sup>2</sup> (5 kg/cm<sup>2</sup>) and about 770 lbs/in<sup>2</sup> (55 kg/cm<sup>2</sup>) on the laminator strip and seam region in order to achieve the invention seam overcoating/lamination result.

[0069] An effective temperature range used for heat treating/laminating an overcoat onto the seam of a typical flexible photoreceptor belt, comprising a top exposed charge transport layer containing a thermoplastic polycarbonate polymer and a dissolved or molecularly dispersed charge transport compound, is appropriately selected to be in a range of between about 85 ° C (185 ° F) and about 97 ° C (206 ° F), based on the fact that the charge transport layer with a thickness of about 24 micrometers has a  $T_g$  of about 82 ° C (180 ° F). Since the preferred imaging member seam lamination treatment embodiment of this invention involves heat and pressure contact with only the seam region (a small surface area), the desired lamination treatment temperature is readily

reached and cooling of the heat treated seam region to room ambient is quickly attained, the entire overcoating/lamination processing is completed within a short cycle time. Generally, the cycle time of the seam overcoating/lamination processing for the typical photoreceptor belt can be accomplished in less than about 20 seconds with the process of this invention for belts having a width of between about 20 centimeters and about 60 centimeters.

[0070]

An alternate heat source and pressure applying system usable in embodiments is illustrated in FIG. 6. A single heated, rotatable compression wheel 150 is rolled over the laminator strip 32 and seam 30 of belt 10, which is parked and held down by vacuum (not shown) on a smooth flat surface of support member 148. The geometry and design of flat support member 148 is identical to the support member 138 shown in FIG. 5. Compression wheel 150 can have a flat outer peripheral surface profile that exerts straight line compression contact against the seam to smooth the exposed surface of seam 30, eliminate protrusions, and reduce the seam region thickness. The direction of the compression force vector is perpendicular to the surface of the support member. The lower edge profile of the peripheral surface of wheel 150 is straight and substantially parallel to the smooth flat surface of the support member 148 during seam treatment. This peripheral surface should be maintained at a temperature sufficient to raise the temperature of the thermoplastic polymer material of the top layer, the imaging layer, of the belt seam to at least its glass transition temperature  $T_g$ . The peripheral surface of wheel 150 preferably has a thin coating surface of adhesive material to prevent imaging layer material from adhering to the peripheral surface of wheel 150 during the seam overcoating/lamination process. Any suitable adhesive material can be used. Typical low surface energy or adhesive materials include, for example, fluoropolymers, such as Teflon, silicone, polyimide, and the like. The heated compression wheel 150 is preferably metallic with a smooth peripheral surface. Heating of the wheel can be accomplished by any suitable device such as, for example, by an electromagnetic induction RF heating mechanism 152 to give the desired temperature when wheel 150 traverses the full width of belt 10 and over seam 30 to compress the seam. Alternatively, any other suitable device, such as a resistance wire heating system 154 can be employed to heat compression wheel 150. Where the resistance wire is part of the wheel, any suitable electrical connection, such

as slip rings 156, can be used to provide electrical energy to the resistance wires. Sufficient heat energy should be supplied to wheel 150 to adequately heat the peripheral surface thereof. Preferably, the hot rotatable compression wheel 150 is reciprocated and the support member 148 carrying belt 10 remain stationary during the seam treatment. However, if desired, the support tube and belt can be moved and the wheel remains stationary or both can be reciprocated to achieve relative motion with each other. Wheel 150 remains rotatable and exerts a linear compression force of between about 1 lb/in. (0.18 kilograms/cm) and about 20 lbs/in. (3.6 kilograms/cm) over the laminator strip and seam region during any of the aforesaid seam treatment embodiments. Since the line force of compressive contact, generated by the continuous rolling wheel pressure action against the laminator strip 32 across the entire belt width, at least matches or is greater than the width of strip 32 at the site on the seam heated by the hot wheel 150, the compressive line of force contact is perpendicular to the seam length and of infinite numbers or continuum as the hot wheel rolls and traverses to effect full seam overcoating/lamination.

[0071]

Another heat source usable in embodiments includes infrared radiation sources. Embodiments can, for example, use incandescent lamps or high intensity discharge lamps as the heat source. Additionally, optics, such as, for example, reflectors, lenses, and filters, can be used to alter the character, path, and intensity of the output of such infrared radiation sources. An example of an infrared radiation heat source arrangement usable in embodiments is illustrated in FIG. 7. A high power tungsten halogen quartz bulb infrared (IR) is the heat source 103, and provides localized, focused IR heating. Preferably, optics are employed to create a small, substantially circular heat spot that preferably straddles the laminator strip 32 after the strip 32 is placed on the seam 30 of imaging member 10. The seam region is, for example, held down on a hollow support cylinder 90 at about the 12 o'clock position. A free rotating compression wheel 108 follows the heat spot to provide localized compression to the heated portions of the laminator strip 32 and the seam region of imaging member 10. The circular IR heat spot should have a diameter sufficient to cover, yet not to exceed, the entire width of the laminator strip 32 in order to impart an effective result. In embodiments, this width can be between about 2 mm and about 15 mm in spot diameter. Compression wheel 108, trailing right behind the IR heat spot, is biased

against the laminator strip 32 (placed over the seam 30) by a spring 110 to provide the needed compression force. Both the IR heat source 103 and compression wheel 108 are supported by any suitable means 112 (partially shown), such as part of the frame of the processing device. An advantage of using a curved, convex surface is to provide seam bending stress release; the processed seam obtained according to embodiments employing such a curved surface can yield an enhanced seam cracking/delamination life extension result under normal operating conditions.

[0072] As in the previous examples, a narrow vacuum channel 104 can be used in embodiments on each side of the hollow support cylinder 90 to hold the belt 10 down against the arcuate convex surface of cylinder 90. The vacuum channels 140 can be about 180 ° apart and extend axially along each side of cylinder 90. Suitable widths for the vacuum channels can be about 60 mils (1.5 mm). One end of tube 90 is sealed (not shown) and the other is connected by a suitable device such as a valved flexible hose (not shown) to any suitable vacuum source. After belt 10 is placed onto the tube 90, such as manually or by any suitable conventional robotic device, the initially closed valve on the flexible hose to the vacuum source is opened, enabling the device to suck the belt 10 against the upper, arcuate, convex surface of tube 90 and to achieve a substantially 180 degree wrapping of belt 10 around the upper, arcuate, convex surface of tube 90. plugs, seals, end-caps, or the like can be used to close the end openings of supporting tube 90 to ensure vacuum buildup. This suction holds the belt 10 substantially immobile on the tube 90 during seam overcoating/lamination processing. If desired, embodiments can include a plurality of holes of any suitable shape (e.g. round, oval, square, and the like) instead of or in addition to the slots 104. The number and size of the holes should be sufficient to hold the belt 10 against the support member. The size of the slots and holes should be small enough to avoid distortion of the belt during the seam area heating and compression process. The resistance of the belt to distortion when suction is applied depends on the beam strength of the specific belt employed, which in turn depends upon the specific materials in and thickness of the layers in the belt 10.

[0073] In embodiments, the supporting cylindrical tube 90 for imaging belt 10 has an outer radius of curvature of, for example, between about 9.5 millimeters and about 50 millimeters (i.e. diameter of curvature of between about 19 millimeters and about 100

millimeters). When the radius of curvature chosen for invention seam overcoating/lamination processing is less than about 9.5 millimeters (i.e. diameter of curvature of about 19 millimeters), the beam rigidity of the electrophotographic imaging belt will raise the belt 10 bending resistance so high that only a very small curvature can be achieved prior to carrying out the treatment. When the radius of curvature is greater than about 50 millimeters (i.e. diameter of curvature of about 100 micrometers), the seam stress-release is not fully realized because little or insignificant seam bending stress-release in the imaging layer is obtained.

[0074]

With reference again to FIG. 7, the electrophotographic imaging belt 10 is positioned with belt seam 30 parked directly over supporting cylindrical tube 90, so that the arcuate convex surface of tube 90 is in intimate contact with the back surface of belt 10 with the top imaging surface of belt 10 facing away from tube 90. If desired, to further assure intimate contact and conformance of the belt to the top convex surface of the tube 90 (say for instance, the belt is making an 180 ° wrap around the tube), a slight belt tension can be applied to the belt 10 by any suitable means such as, for example, by inserting a light weight cylindrical tube of the same outer diameter as tube 90 inside the lower loop of belt 10 while the belt 10 is hanging from tube 90. Tube 90 can be cantilevered by securing one end to a supporting wall or frame. A desirable imaging member wrapped angle for the seam segment parking over the back supporting cylindrical tube 90 should provide an arcuate convex area at the seam region at least about as wide as the diameter of the heated substantially circular IR spot. It is preferred that the wrap angle encompassing the seam and region of the belt adjacent each side of the seam conforming to the arcuate convex supporting surface of the support member be between about 10 ° and about 180 ° . The material used for tube 90 must be very hard and nearly incompressible. It can be of any suitable material, including, for example, metal, plastic, composites, and the like, but is preferably metallic. Although the imaging member 10 is shown to be held down against the convex upper surface of the full circular support tube 90 in FIG. 7, the elongated support member may alternatively have any other suitable shape such as an elongated half circle, an elongated partial circle, a bar having an arcuate convex surface on the side contacting the seam, and the like, provided the support member employed has an arcuate convex curve surface sufficient to retain and hold down the

entire length of the seam region of the parked belt during seam overcoating/lamination processing.

[0075]

The IR tungsten halogen quartz bulb 105 emits a dominant radiant wavelength of about 0.98 micrometer. Preferably, at least about 80 percent of the radiation emitted by the tungsten halogen quartz bulb 105 has a radiant wavelength of about 0.98 micrometer. A typical, commercially available, high powered IR tungsten halogen quartz bulb 105 that can be used in heating source 103 is a Model 4085 infrared heating bulb, available from Research, Inc., and comprises a 750 watt tungsten halogen quartz bulb (750Q/CL, available from Research, Inc.) positioned at a focal point inside an aluminum hemi-ellipsoid shaped heat reflector 106 similar to the schematic arrangement shown in FIG. 7. This IR heating bulb 105 has an adjustable energy output to give suitable IR heat spot temperature; for example, with heat flux densities to 650 watts per square inch (1007 kilowatts per square meter) at a 6 millimeter diameter focal point of the converging infrared energy. A 500 watt tungsten halogen quartz bulb is also available from Research, Inc., and other suitable bulbs could be obtained from other manufacturers. Bulb 105 is positioned inside an hemi-ellipsoid reflector 106 at the focal point of the reflector so that all the reflected energy from bulb 105 converges at another focal point outside of the reflector 106. If the hemi-ellipsoid reflector were formed into a complete ellipsoid rather than half an ellipsoid, there would be two symmetrically positioned focal points, one where the bulb 105 is located and the other where the reflected energy from the bulb 105 converges. The reflector can be made of any suitable coated or uncoated material. Typical materials include, for example, uncoated aluminum, gold plated metal, stainless steel, silver, and the like. If desired, the reflector can contain openings to facilitate the circulation of a cooling gas. An increase in the area of the openings in the reflector will reduce the amount of reflected energy from bulb 105 that converges at another focal point outside of the reflector 106. The distance between the reflector and the outer surface of the seam is adjusted by any suitable positioning device, such as, for example, a conventional lead screw and ball device 88. Any other suitable device, such as a rod fixed to a movable carriage and sliding collar fitted with a set screw, the collar being secured to the reflector and slidable on the rod, can be used so long as a high intensity, substantially circular IR spot can be formed. The diameter of

the spot is, for example, between about 2 millimeters and about 15 millimeters and covers the entire width of the laminator strip 32. this high intensity focused circular IR spot substantially instantaneously elevates the temperature of only a small localized region, sufficient enough to cover the width of the laminator strip 32 and to exceed the glass transition temperature ( $T_g$ ) of the charge transport layer in the seam area or the laminate 34 of laminator strip 32. Typically, the  $T_g$  of a film forming polymer in the formulation used for electrophotographic imaging layer coating applications is at least about 45 ° C to satisfy most imaging belt machine operating conditions. Preferably, the heat exposure spot in embodiments should be between about the 20 ° C and about 70 ° C above the lower of the  $T_g$  of the imaging layer or the laminate 32 to achieve sufficient seam overcoating/lamination and stress release results.

[0076] the IR heating source 103 is moved substantially continuously or incrementally, along and above, the laminator strip 32 and the seam 30, by manually or automatically means, such as by any suitable horizontally reciprocateable carriage system (not shown). Typical horizontally reciprocateable carriage systems include, for example, ball screw, two way acting air cylinder, lead screw and motor combination, belt or chain drive slide system, and the like. A relative speed of movement between the heating source/compression wheel assembly and the support tube 90 holding the seamed belt 10 can be from about 1 centimeter to about 20 centimeters per second with satisfactory results. A relative speed between about 2.5 centimeters and about 12.5 centimeters per second yields better results. Alternatively, if desired, the whole integral part of the IR heat source 103 with compression wheel assembly can be held stationary while the tube 90 carrying the hold-down imaging member can be set to motion, in exact but reversed manners as just described, to achieve the same processing outcome.

[0077] The rotatable compression wheel 108 illustrated in FIG. 7 can have a peripheral surface with an arcuate, concave cross section with a curvature that substantially corresponds to or is slightly larger than the predetermined curvature of the arcuate, convex, substantially semicircular cross section of the elongated surface of the upper half of the support tube 90. The wheel 108 produces a compression line pressure contact between the peripheral surface of the wheel and outer surface of the seam, augmented by tension force generated by spring 110. To produce effective invention

seam area overcoating/lamination result that can yield good seam region physical continuity and an improved surface morphological profile, it is important that the peripheral surface of the compression wheel has an arcuate concave radius of curvature. Preferably, the arcuate concave radius of curvature is between about 9.5 millimeters and about 55 millimeters. The arcuate concave radius of curvature should correspond to or be slightly larger (e.g., by up to about 10 percent larger) than the convex surface radius of curvature of the support tube 90, which preferably has a convex radius of curvature of between about 9.5 millimeters and about 50 millimeters. The radius of the compression wheel 108, measured from its center of rotation or axis to the midpoint of line contact against the seam, can be, for example, between about 1/8 inch (3.2 millimeters) and about 1/2 inch (12.7 millimeters), so long as the pressure application requirements of embodiments are met. Measurement of the radius of the compression wheel 108 is analogous to measuring the radius at the waist of an hour glass, the compression wheel 108 having a cross sectional shape (taken along the axis of the hour glass) similar to that of an hour glass.

[0078]

Since the heated localized site cools very quickly, a very small compression wheel radius measured at the waist allows delivery of the circular hot spot from the IR heat source 103 to the laminator strip (placed over the seam) closer to the imaginary axis of the wheel or the line of compression so that it is in tangential contact with waist of the wheel (e.g., bottom of the arcuate channel at about the 3 o'clock position of the wheel when a vertically aligned compression wheel is employed). Preferably, contact of the IR heat spot to the waist or any other part of the wheel 108 is avoided to prevent heat build up in the wheel. By positioning the focus beam of the IR close to the waist of a small radius wheel, the localized site heated by the IR heat spot is very close to the line of compressive contact exerted by the compression wheel against the laminator strip 32 from one side of the seam region to the other which, therefore, allows quick compression force application by the wheel to the localized heated spot before this hot spot cools to a temperature below the  $T_g$  of heated polymer material in the localized site and thereby effecting seam overcoating/lamination result. However, the radius at the waist of the wheel should not be so small that rigidity of the compression wheel is compromised. Thus, for example, the waist radius of the compression wheel should not be so small as to cause the wheel or wheel support

member to bend when it is used to apply a compression force to the seam region. The limiting waist radius of the wheel 108 is strongly dependent on the specific materials used to make the wheel. Similarly, bending resistance is also dependent on the specific materials selected for the wheel.

[0079] If desired, embodiments of the IR heat source 103 can be designed to have varying adjustable positions such that it can be tilted, inclined, or angled to allow positioning of the incident focused IR heat spot even closer to the line of compressive contact between the compression wheel 108 and the laminator strip/seam region. Since the line of compressive contact generated by the rolling compression wheel contacting the laminator strip/seam region is greater than or equal to the laminator strip width, the lines of compressive contact force generated are substantially perpendicular to the seam length and of infinite number. This achieves substantially complete seam overcoating/lamination processing with seam smoothing, stress-release, and substantial reduction of physical discontinuities of the entire seam region. Therefore, it is preferable that the line of compressive contact made by the compression wheel 108 on the laminator strip 32 form an arc of sufficient length to cover the full width of the laminator strip 32. The circumferential concave surface of the compression wheel 108 preferably generates a uniform linear compression force of, for example, between about 1 lb/in (0.18 kilograms/cm) and about 20 lbs/in (3.6 kilograms/cm) when in rolling contact with the laminator strip 32. By comparison, if a compression wheel 108 having a peripheral surface with a cross section having an infinite radius of curvature (which is essentially a straight line) is used, only point contact is achieved since support member surface is arcuate. The compression wheel 108 can be of any suitable material, including, for example, metallic, hard plastic, or composite materials having a smooth contacting surface. It is preferred that the contacting surface comprises a thin coating of low surface energy material, such as a fluoropolymer, such as Teflon, polysiloxane, a polyimide, such as Kapton, and the like.

[0080] In the event that it is required to process a flexible imaging member having a slanted seam (i.e. a seam that is an angle other than 90 degrees with each edge of belt 10), the integral part of heating source 103 and compression wheel assembly may be programmed or set to precisely track the seam when traversing the entire belt

width. However, it is preferred that the belt be cocked and adjusted so that the seam is parallel to an imaginary axis of the support cylinder member (i.e., without skewing) along the top of the support cylinder member after belt mounting.

[0081] Although the IR heat source 103 is shown as a quartz halogen lamp in FIG. 7, any other suitable source of heat energy can be used as the IR heat source 103. For example, embodiments can use an IR laser, such as a sealed carbon dioxide ( $\text{CO}_2$ ) laser, as the IR heat source 103, as is illustrated, for example, in FIG. 8. Sealed carbon dioxide ( $\text{CO}_2$ ) lasers are commercially available, such as a Model Diamond 64 sealed carbon dioxide laser from Coherent, Inc., which is a slab laser comprising a pair of spaced apart, planar electrodes having opposed light reflecting surfaces. The spacing of the electrodes is arranged such that light will be guided in a plane perpendicular to the reflecting surfaces, while light in a plane parallel to the light reflecting surfaces is allowed to propagate in free space and is only confined by a resonator. Preferably, the lasing medium is a standard  $\text{CO}_2$  lasing mixture, including, for example, helium, nitrogen, and carbon dioxide with a 3:1:1 ratio, plus the addition of five per cent xenon. The gas is maintained between 50 and 110 torr and preferably on the order of about 80 torr. The gas is electrically excited by coupling a radio frequency generator between the electrodes, as is explained in the description of a typical sealed carbon dioxide laser found, for example, in U.S. Patent Number 5,123,028, the entire disclosure of which is incorporated herein by reference. Sealed carbon dioxide lasers are also described in U.S. Patent Number 5,353,297, U.S. Patent Number 5,353,297, and U.S. Patent Number 5,578,227, the entire disclosures of which are also incorporated herein by reference. While such sealed carbon dioxide lasers can produce, for example, a 150 watt beam, when used in embodiments, such lasers should be adjusted to deliver a lower output of, for example, about 6 watts for the seam heat treatment process.

[0082] Optics are employed in embodiments to treat the output of the laser. A phase shift mirror can be used to transform a laser beam with linear polarization into a beam with circular polarization. To obtain a circularly polarized beam, a phase shift mirror is positioned with an incidence angle of 45 degrees and the laser beam output with a plane of polarization parallel to the laser base is rotated 45 degrees to the plane of incidence. The resulting circularly polarized beam of heat energy is focused with a

lens into a desired size on the outer surface of the seam. For example, a Melles Griot Zinc Selenide Positive Lens with focal distance of 63.5 mm (2.5 inches) can be used as the image lens. In the process of the present invention, all of the radiant energy emission from the carbon dioxide laser 103 progressively strikes localized sites encompassing the seam and regions of the imaging belt immediately adjacent the seam to deliver instant heating followed by quick cooling as the belt 10 with the supporting cylindrical 90 is traversed by the beam of heat energy from the laser heating source.

[0083]

Preferably, the raw laser heat energy beam emitted from a laser has a circular cross section, but any other suitable cross sectional shape can be used to raise the temperature of a localized site along the seam. The diameter of a raw beam emitted by a laser is normally constant along the entire length of the beam. The thermal energy radiation emitted from a carbon dioxide laser is directed at the seam of the belt and the thermal energy radiation from the laser forms a localized site, such as a round spot, straddling the seam during traverse of the seam. The heated localized site, such as a round spot, on the surface of the seam preferably has an average width of between about 3 millimeters and about 25 millimeters measured in a direction perpendicular to the imaginary centerline of the seam, depending upon the particular dimensions of the seam to be treated. For example, a Model Diamond 64 sealed carbon dioxide laser from Coherent, Inc., has a circular raw heat energy beam having a diameter of about 6 millimeters. This raw laser heat energy beam will form a heated localized site or spot having a diameter of about 6 millimeters on the belt seam. If desired, the 6 millimeter spot size of the thermal energy striking the outer surface of the seam can be reduced for small seam area heating by masking the emitted raw laser heat energy beam using any suitable device, such as a metal template, to give a 3 millimeter to 6 millimeter heated localized spot size measured in a direction perpendicular to the imaginary centerline of the seam. Although the template can alter the heated localized spot shape to any suitable and desired shape such as an oval, square, rectangle, hexagon, octagon and the like, a circular heated localized site or spot is preferred. Moreover, where for example, the laser heat energy beam has a diameter of about 6 millimeters and a larger heat spot is desired on the outer surface of the belt seam, the laser beam can be defocused using any suitable device, such as a

zinc selenide lens between the laser beam source and the belt seam. Thus, by varying the relative distances between the laser beam source, the lens and the belt seam, the 6 millimeter diameter laser beam can be defocused to give a larger spot having a diameter greater than about 6 millimeters and preferably less than about 25 millimeters in diameter measured in a direction perpendicular to the imaginary centerline of the seam for stress release treatment of large seam areas. If a mask is employed to change the shape of the raw laser heat energy beam or the defocused heat energy beam to form a spot shape other than round, the preferred heated localized site or spot size that straddles the seam has an average diameter between about 3 millimeters and about 25 millimeters measured in a direction perpendicular to the imaginary centerline of the seam. When the average diameter of the heated localized site measured in a direction perpendicular to the imaginary centerline of the seam is less than about 3 millimeters, the resulting stress release area is not enough to cover a seam region which has a width of about 3 millimeters from one side of the seam region to the other. When the average diameter of the heated spot is greater than about 25 millimeters, the stress release area exceeds the intended seam treatment region and extends into the electrophotographic imaging zone of the belt normally used for image formation.

[0084]

Since the carbon dioxide laser delivers a constant diameter raw heat energy beam, the physical distance from the seam surface of the imaging belt to the laser is less important for the heat treatment process of this invention, as long as the intended seam heat treatment spot size is the same as the diameter of the raw laser beam or smaller than the raw laser beam by using a masking template. the carbon dioxide laser spot substantially instantaneously elevates the temperature of polymer material in only a small localized region or site of the imaging layer of the imaging member above the glass transition temperature ( $T_g$ ). Although the thermoplastic polymer material must be heated to at least the glass transition temperature thereof, such heated polymer material need be only in the upper portion of the seam area to achieve the seam treatment objectives of this invention. However, if desired, heating of the seam region completely through the thickness or cross-section thereof can be accomplished during heating of a localized site. Elevation of the temperature of only a small localized region or site along the seam from one edge of the belt to the other to

at least the glass transition temperature of the thermoplastic polymer material is accomplished progressively as the heat energy beam traverses the width of the belt along the seam.

[0085] An alternative heat source, a variation of that shown in FIG. 7, employs an elongated focused IR emitting source that can include, for example, an elongated halogen quartz tube coupled with a hemi-ellipsoidal shaped cross-section elongated reflector. The elongated focused IR emitting source is positioned above the seam laminator strip and covers the entire width of the imaging member 10. The elongated focused IR source thus delivers an IR focused heating line to heat the entire laminator strip 32 and seam 30 at once. The width of the focused IR heating line should cover the width of the laminate 34 of the laminator strip 32. The heated strip and seam can then be compressed, as with a rolling wheel 108 (or a heated rolling wheel 115 according to that shown in Figure 9), while the belt 10 is belt down over the arcuate convex surface of tube 90, to complete the seam overcoating/lamination treatment. Such a focused IR heating line can also be used in embodiments according to the process and apparatus of FIG. 6 where an externally-heated or cold compression rolling wheel 150 is used, while belt 10 is held down over the surface of flat support 148.

[0086] FIG. 9 illustrates another alternative embodiment of seam overcoating/lamination process and apparatus similar to that shown in FIG. 7. A single, internally-heated compression wheel 115 is employed to heat and compress the seam 30 of a belt 10 situated and held down with vacuum on an elongated support tube 90. The peripheral surface of wheel 115 has an arcuate concave cross section having a curvature which corresponds to or is slightly larger than the curvature of the arcuate convex surface of the elongated surface of the upper half of support tube 90. This peripheral wheel surface should be maintained at a temperature sufficient to raise the temperature of the thermoplastic material in at least the upper half of the belt seam to its glass transition temperature  $T_g$ . The peripheral surface of wheel 115 also preferably has a thin coating surface of adhesive material, such as a fluoropolymer, such as Teflon, and the like to prevent imaging layer material from adhering to the wheel surface during the seam treatment process. The heated compression wheel 115 is preferably metallic with a smooth peripheral surface. Heating of the wheel can be accomplished

by any suitable device such as, for example, by an electromagnetic heating mechanism 116 to give the desired temperature when wheel 115 traverses the width of belt 10 along on the seam 30. Alternatively, any other suitable device, such as a resistance wire heating system 117 can be employed to heat compression wheel 115. Where the resistance wire is part of the wheel, any suitable electrical connection such as slip rings 118 can be used to provide electrical energy to the resistance wires. Sufficient heat energy should be supplied to wheel 115 to adequately heat the peripheral surface thereof. Preferably, the hot rotatable compression wheel 115 is not reciprocated and the support tube 90 carrying belt 10 is moved during the seam treatment. However, if desired, the support tube and belt can be stationary and the wheel reciprocated or both can be reciprocated to achieve relative motion with each other.

[0087] Thus, the process and apparatus of embodiments as shown in the examples described above produce a flexible imaging member in which the seam has a protective overcoating substantially free of protrusions, a smooth surface profile, and that exhibits good physical continuity. Additionally, the seam area produced by embodiments has reduced seam area thickness and enjoys reduced fatigue induced bending seam stress cracking under dynamic belt flexing conditions over the rollers a belt support module during imaging machine operation. Furthermore, treating according to embodiments can substantially enhance imaging member production yield, effectively reducing the belt unit manufacturing cost. Because successful implementation of embodiments greatly reduces or substantially eliminates the need of labor-intensive and time-consuming manual seam inspection procedures, embodiments also effectively increase production belt yield by recovery of those belts that are otherwise lost as rejects due to the presence of seam protrusions. Thus, embodiments deliver a seam configuration with significantly improved qualities, better physical/mechanical attributes, such as smoother surface profile, absence of protrusion spots, thinner cross-section thickness, and little or no physical discontinuity to enhance cleaning blade performance and suppress the premature onset of fatigue induced seam cracking/delamination problem during extended electrophotographic imaging and cleaning processes.

[0088] It should be noted that, though embodiments use a treatment article or strip with

the thermoplastic polymer film on a carrier/support substrate, such as that shown in FIG. 4, the present invention can be performed with a treatment article or strip including a single layer of thermoplastic polymer with no carrier/support substrate.

[0089] A number of examples are set forth hereinbelow and are illustrative of different compositions and conditions that can be used in practicing embodiments. All proportions are by weight unless otherwise indicated, are exemplary in nature, and are not limiting to the invention. It will be apparent that the invention can be practiced with many types of compositions and can have many different uses in accordance with the disclosure above and as pointed out hereinafter.

[0090] *EXAMPLE I: Belt Preparation*

[0091] An electrophotographic imaging member web was prepared by providing a roll of titanium-coated, biaxially-oriented thermoplastic polyester substrate. The substrate comprised PET, Melinex (available from ICI Americas, Inc.) and had a thickness of 3 mils (76.2 micrometers). A blocking layer with a dry thickness of 0.05 micrometer was formed on the substrate, on which an adhesive interface layer was then prepared with a dry thickness of 0.07 micrometer. The adhesive interface layer was thereafter coated with a photogenerating layer with a dry thickness of 2.0 micrometers. However, a strip about 3 mm wide along one edge of the coating web, having the blocking layer and adhesive layer, was deliberately left uncoated by any of the photogenerating layer material to facilitate adequate electrical contact with the ground strip layer that is applied later. Next, a charge transport layer and a ground strip layer were applied by co-extrusion of the coating materials. The uncoated portion of the adhesive layer was included in the application of the ground strip layer. Finally, an anti-curl coating was applied to the rear surface (side opposite the photogenerator layer and charge transport layer) of the electrophotographic imaging member web to produce a dried coating layer having a thickness of 13.5 micrometers.

[0092] The charge transport layer was prepared by introducing into an amber glass bottle in a weight ratio of 1:1 (or 50% wt of each) N,N'-diphenyl-N,N'-bis(3-methylphenyl)-1,1'-bisphenyl-4,4'-diamine and Makrolon 5705, a Bisphenol A polycarbonate thermoplastic having a molecular weight of about 120,000 commercially available from Farbensabricken Bayer A.G. The resulting mixture was dissolved to give 15

percent by weight solid in methylene chloride. This solution was applied on the photogenerator layer by extrusion to form a coating which upon drying gave a thickness of 24 micrometers.

[0093] The prepared electrophotographic imaging member web had a width of 353 millimeters and was cut to provide five rectangular sheets each 559.5 millimeters in length for flexible imaging member seaming operation. The opposite ends of each imaging member were overlapped 1 mm and joined by an ultrasonic energy seam welding process using a 40 KHz horn frequency to form a seamed electrophotographic imaging member, having a top seam splashing surface morphology 74 and displaying a physical discontinuity step 72 with a junction point 76 according to the illustration in FIG. 2. Four of the five seamed belts were ready to be used for invention seam overcoating/lamination processing while one of the remaining unprocessed seamed belt was used to serve as a control.

[0094] EXAMPLE II: Treatment Article Preparation and Application

[0095] *No Substrate*

[0096] Six thermoplastic polymer coating solutions were prepared by dissolving Makrolon 5705 polycarbonate with varying amount of charge transport compound N,N'-diphenyl-N,N'-bis(3-methylphenyl)-1,1'-bisphenyl-4,4'-diamine in methylene chloride. The prepared solutions were each applied over a releasing substrate and dried at 257 ° F (125 ° C) in an air circulating oven for 5 minutes to rid the solvent and then removed from the release substrates to give thermoplastic polymer layers containing 0% wt, 10% wt, 20% wt, 30% wt, 40% wt, and 50% wt charge transport compound in each respective 25 micrometer thick layer. The thermoplastic polymer layers were each analyzed for glass transition temperature,  $T_g$ , using differential scanning calorimetric method. The results obtained, listed in the table below, showed that the addition of charge transport compound to the Makrolon could provide successive suppression of the  $T_g$  of the resulting polymer layer:

[0097]

[t2]

--	--

<i>POLYMER LAYER</i>	$T_g (^{\circ}C)$
0% wt	156
10% wt	135
20% wt	120
30% wt	104
40% wt	91
50% wt	84

[0098] A 5 mm width strip was cut from the thermoplastic polymer layer containing 50% by weight charge transport compound (essentially identical to the charge transport layer of the electrophotographic imaging member of Example I) and placed over the top seam splash 68 (refer to seam morphology description in FIG. 2) of one welded electrophotographic imaging member of Example I, which was vacuum held down, to overcoat/laminate the seam region by heat and compression processing as that in FIG. 5. The compression pressure exerted by the hot compression bar was approximately 200 lbs/in<sup>2</sup> and with a temperature of about 130 ° C to effect the seam overcoating/lamination outcome.

[0099] Since the processing was carried out at a temperature 46 ° C above the  $T_g$ , the overcoat laminate became compressible as well as malleable under the applied pressure to readily fuse onto the seam and fill-up the seam step junction 76.

[0100] EXAMPLE III: Treatment Article Preparation and Application

[0101] *Substrate*

[0102] A coating solution , prepared by dissolving 10 grams of Makrolon in 90 grams of solvent mixture consisting of 90 parts of methylene chloride and 10 parts of toluene, was applied to a 3-mil thick, biaxially-oriented PET substrate by hand coating using a Bird applicator. The coated wet Makrolon layer was allowed to dry under room ambient conditions for 15 hours to produce a 35-micrometer thick solid polymer layer containing 60% by weight Makrolon and approximately 40% by weight toluene, with only a small amount of residual methylene chloride since toluene was much less

volatile than methylene chloride. The resulting coating layer over PET substrate was cut to give an 8 mm width strip. The coating layer in this 8 mm strip was cut at both sides, through only the Makrolon layer not the PET, to remove 2 mm of Makrolon coating layer from each side to create a laminator strip 32, like that illustrated in FIG. 4, which consists of a 4 mm width thermoplastic polymer laminate 34 adhered onto an 8 mm wide flexible PET carrier substrate 36.

[0103] The fabricated laminator strip 32 was positioned over the seam of the second welded electrophotographic imaging member of Example I and then subjected to the inventive seam overcoating/lamination processing, carried out with the same procedures and apparatus as described in Example II. Since the laminate strip 34 was loosely adhered to the PET carrier substrate 36 (only about 6 grams/cm 180 ° peel strength), it was easily removed from the seam overcoat after completion of the heat/compression application. The resulting overcoated seam had been found to obtain about equivalent physical and morphological attribute improvements seen in the treated seam of Example II.

[0104] EXAMPLE IV: Treatment Article Preparation & Application

[0105] *Solution of Example II on Substrate; IR Lamp and Wheel on Tube*

[0106] A laminator strip 32 was prepared, using a coating solution according to Example II and a 3-mil thick biaxially oriented PET substrate, according to the procedures described in Example III, to give a 25-micrometer thick polymer laminate 34, containing 70% by weight Makrolon and 30% by weight charge transport compound, over PET carrier substrate 36. The surface of laminate 34 of the prepared laminator strip 32 was first brushed (using a small soft paint brush) with small amount of methylene chloride to moisten the surface and thereby promote some adhesion to the seam region surface for ease of anchoring the laminator strip 32 directly onto the seam of the third welded electrophotographic imaging member of Example I, which was held down over a 2-inch diameter tube 90 as illustrated in FIG. 7. The overcoating/lamination processing used an IR heat source 103 to provide a focused, 8 mm diameter hot spot for localized heating of the laminator strip 32 to a temperature of 120 ° C. The hot spot was followed with a free rotating compression wheel 108 to generate an 8 lbs/in compression line for effective seam overcoating/lamination

result.

[0107] The heating and compression procedures to achieve the invention seam overcoating/lamination result were carried out according to embodiments such as that illustrated in FIG. 7 and given in the preceding text of this specification. Since the laminate 34 was loosely adhered to the PET carrier substrate 36, the PET was readily peeled off from the overcoated seam after the processing.

[0108] EXAMPLE V: Treatment Article Preparation and Application

[0109] *Treatment Article of Example IV; IR Laser and Wheel on Tube*

[0110] A laminator strip 32 was again prepared, in exact same manners described in Example IV, to give a. laminate 34 having 25 micrometers in thickness and containing 30% by weight charge transport compound over PET carrier substrate 36.

[0111] To effect invention seam treatment processing, the fourth welded electrophotographic imaging member 10 of Example I was suspended (as shown in the illustration of FIG. 7) over a horizontally movable cantilevered supporting aluminum tube 90, having a 2-inch (5.08 centimeters) diameter, a wall thickness of about 0.25 inch (6.35 millimeters), and an anodized outer surface, with the welded seam 30 parked directly along the top (i.e. 12 o'clock position) of the support tube 10 and being parallel to the axis of the tube. The tube 10 contained a pair of slots 10, with one slot at the 9 o'clock position and the other at the 3 o'clock position. Each slot extended along the length of the imaging member width and was 2 millimeters wide. The free end of the tube 10 was sealed by a cap and the supported end was connected to a flexible hose leading through a valve to a vacuum source. The vacuum source was maintained at a pressure of about 40 mm Hg. The belt in the seam area was held down against the upper arcuate convex surface of the supporting tube when the valve to the vacuum source was opened so that the seam area conformed to the shape of the upper surface of the tube. The laminator strip 32, having the surface of the laminate 34 moistened with methylene chloride was placed directly over the seam give some adhesion hold down onto the seam region for ease of carrying out the heat/compression seam lamination process. The temperature of a localized circular spot, about 8 mm in diameter, of the laminator strip 32 and the respective covering

seam region was raised to about 120 ° C using a sealed carbon dioxide laser heating source 103 (Model Diamond 64, available from Coherent, Inc.) instead of the focused IR of Example IV. The laser heat source 103 had an adjacent trailing free rotating compression wheel attachment, as shown in FIG. 8, which was adjustable to deliver an about 8 lbs/cm compression line over the heat spot by spring 110, to effect the heat/compression process.

[0112] This invention seam treatment processing was then carried out according to the schematic illustration of FIG. 7. The carbon dioxide laser heating source had a 150 wattage power capability, but for the purpose of present seam treatment process, it was adjusted to deliver an energy output of only about 5.6 watts at an 8 millimeter diameter of raw laser beam spot. an infrared sensing camera was employed to adjust laser delivery of 150 Hz, 50 microsecond pulse duration, and a seam traversing speed of 2 in/s (5.08 cm/s) to ensure that the heat spot on laminator strip for seam treatment temperature reached 120 ° C. A spot temperature of 120 ° C was sufficient to soften the laminate 34 and the charge transport layer beneath the laminate 34 for effectual application of the overcoating laminate to smooth out surface profile, fill the seam splash junction 76 to thereby eliminate the physical discontinuity, and yield seam stress-release result. The laser heat source emitted a dominant radiant wavelength of 10.64 micrometers and formed a substantially circular laser spot of about 8 mm in diameter incident over and straddling the laminator strip and seam area to provide instant heating result in the localized site to effect such heating progressing along the length of the seam, as the support tube 90 with the held down belt 10 were moved under the laser heat source/compression wheel assembly at a traversal speed of 2 in/s (5.08 cm/ss) and exerting about 20 pounds of rotating wheel compression force by the spring 110 to yield a 4 mm line contact over the laminator strip and the covering seam region; accordingly, the rotating wheel generated an compression line force of about 8 lb/cm linear width . The entire seam heat/compression and overcoating/lamination processing carried out for each imaging member was completed in about seven seconds.

[0113] *EXAMPLE VI*

[0114] The invention seam overcoating/lamination processing carried out for the seamed

electrophotographic imaging member belts described in Examples II to V was seen to give overcoat laminate that was strongly bonded to the welded seam region, since the laminate used was essentially made of the same materials and chemical components of the seam. Therefore, the end result of the seam overcoating/lamination was that the laminate was fused onto the seam area and became an integral part of the seam, which eliminated the physical discontinuity to display a tapering surface topology without the seam splash junction 76. Further seam surface roughness analysis of these seamed belts before and after treatment, using a Wyko Gauge surface analyzer, showed that the original seam splash surface roughness was significantly reduced from an average high Ra value of 6.3 to a low value of 1.6. The inventive treatment process was also found to produce a slight overall reduction in seam area thickness of up to about 10 percent.

[0115] The control electrophotographic imaging member of Example I and the four seam overcoated electrophotographic imaging members obtained through the treatment process of the present invention described by Examples II to V were each dynamically cycled and print tested in a xerographic machine, having a belt support module comprising a 25.24 mm diameter drive roller, a 25.24 mm diameter stripper roller, and a 29.48 mm diameter tension roller to exert on each belt a tension of 1.1 pounds per inch. The belt cycling speed was set at 65 prints per minute.

[0116] The control imaging member of Example I, having no seam overcoat laminate, was cyclic tested to only about 56,000 prints and terminated for the reason of developing onset of seam cracking/delamination problem.

[0117] When the very same belt cycling procedure was repeated with each of the imaging members through the process of the present invention, neither seam failure nor notable ripple appearance in the image zones were observed after completion of 500,000 prints of belt cyclic testing. Further, minimal cleaning blade wear was observed after completion of 500,000 prints of belt cyclic testing.

[0118] In recapitulation, the seam overcoating/lamination process of the present invention resolves seam cracking/delamination problems, provides a very short treatment processing cycle time, substantially eliminates seam splash junction physical discontinuity, substantially prevents the appearance of ripples in the imaging

zones adjacent to the seam heat treatment area, provides smoother surface profiles, produces dimensionally stable imaging members, suppresses cleaning blade wear, and yields a processed seam substantially free of high protrusion spots to thereby reduce seamed imaging member rejection rates, which increases imaging member production yield.

[0119] Although the invention has been described with reference to specific exemplary embodiments, it is not intended to be limited thereto. Rather, those having ordinary skill in the art will recognize that variations and modifications may be made therein which are within the spirit of the invention and within the scope of the claims.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2